

M2M Global Technology Intelligent Multi Network Switching Sim Technology

Product Catalogue





About Us

M2M Global Technology Limited is a world leader in total GPS/GSM/WCDMA tracking, location and alarming solutions. With a vast range of in-house services M2M Global Technology is positioned to help you make the most of your opportunities.


With 23 offices in 17 countries around the world, and 5 emergency response centres offering emergency assistance in 6 languages, M2M Global Tech are the leading global security and asset tracking company. Our units operate across all GSM and WCDMA platforms, and using M2M's world first Intelligent Multiple Network Switching sim technology will work on almost any GSM network worldwide.





Content

About Us	02
Content	.03
Protect – Product Features and Specifications	.04
Track – Product Features and Specifications	.06
Watch – Product Features and Specifications	.08
QT 1000 Series Specifications	.10
QT 209 EnduroTrack Specifications	.12
QT 1100 QuikLock Specifications	.14
QT 1200 WatchTrack Specifications	.16
Product Benefits	.17
IMNS SIM Technology	.18
Our Contacts	.19









Product Features

- · Location on Demand,
- Internal Battery,
- User pay credit system (no monthly fees!)
- 10 free credits upon activation,
- 24/7 Customer Support,
- 24/7 Stolen Asset Recovery Assistance,
- IMNS Sim Technology (domestic and global roaming!),


- Remote Immobilisation (optional),
- Smartphone Applications,
- Optional Annual Warranty Program.


Device Specifications

Voltage:	6 – 36V
Work Current:	< 30mA @ 36V
Standby Current:	< 5mA @ 12V
GPS Accuracy:	5m
LBS Accuracy:	10m
GPS Sensitivity:	-159dBm
GSM Frequency:	850 / 900 / 1800 / 1900MHz Quad band
WCDMA Frequency:	W900 / W2100MHz
Hot/warm/cold Start:	< 3s, < 15s, < 45s
Battery Capacity:	370mAh
Dimensions (mm):	68(L) x 40(W) x 20(H)
Work Temperature:	-20°C – 70°C
Work Humidity:	20% – 80% RH
Weight:	90 gram
IP Level:	IP 67









Product Features

- · Live location updates,
- Internal Back up Battery,
- 24/7 Online Customer Support,
- 24/7 Stolen asset recovery assistance,
- Historical Playback (bread crumb trail),
- Activity Reports (moving and stationary),
- Route optimisation (improving accuracy and reducing update times),

- IMNS Sim Technology,
- · Idle reporting,
- Engine hours and mileage reporting,
- Engine usage logs,
- Servicing intervals,
- · Geofencing and alarming,
- Customisable alarms,
- Remote immobilisation (optional).

Device Specifications

Voltage:	12 / 24 / 36VDC
Work Current:	< 30mA @ 12V
Standby Current:	< 10mA @ 12V
GPS Accuracy:	5-15m (Depend GPS signal)
LBS Accuracy:	200m (Depending on density of base stations)
GPS Frequency:	1575MHz
GSM Frequency:	850 / 900 / 1800 / 1900MHz
WCDMA Frequency:	W850 / W1900 / W2100MHz
Hot/warm/cold Start:	< 3s, < 15s, < 60s
Battery Capacity:	250mAh
Dimensions (mm):	87(L) x 41.6(W) x 12(H)
Work Temperature:	-20°C – 70°C
Work Humidity:	20% – 80% RH
Weight:	175 gram
IP Level:	IP 67



- Driver Identification tags,
- Immobilise without tags (optional).




- Tilt/shock sensor
- Tamper alarms
- Ignition alarms,
- Immobilisation without disarm (optional),
- Remote arm/disarm.



- Bilge notification,
- Shore power disconnection,
- Low battery voltage,
- Intrusion alarms.





Product Features

- · Live location updates,
- Internal Back up Battery,
- 24/7 Online Customer Support,
- · 24/7 Stolen asset recovery assistance,
- · Historical Playback (bread crumb trail),
- Activity Reports (moving and stationary),
- Route optimisation (improving accuracy and reducing update times),

- IMNS Sim Technology (domestic and global roaming!),
- · Idle reporting,
- Engine hours and mileage reporting,
- Engine usage logs,
- Servicing intervals,
- · Geofencing and alarming,
- Customisable alarms/inputs.

Device Specifications

Voltage:	10.6V – 36V / 1.5A
Work Current:	< 30mA @ 12V
Standby Current:	< 10mA @ 12V
GPS Accuracy:	10m, 2D RMS
LBS Accuracy:	200m (Depending on density of base stations)
GPS Frequency:	L1-band (1575.42MHz)
GSM Frequency:	850 / 900 / 1800 / 1900MHz Quad band
WCDMA Frequency:	W850 / W1900 / W2100MHz
Hot/warm/cold Start:	< 1s, < 38s, < 42s
Battery Capacity:	500mAh
Dimensions (mm):	65(L) x 61(W) x 26(H)
Work Temperature:	-20°C – 65°C
Work Humidity:	5% – 95% Non condensing
Weight:	90 gram
IP Level:	IP 67





QT 1000 Series

QuikTrak series **QT 1000** is a dual mode GSM/IRIDIUM GPS tracker that works anywhere in the world, using GSM networks where available, switching seamlessly to the SBD Iridium network when no GSM network is available.


Utilising QuikTrak's IMNS SIM the **QT 1000** roams seamlessly worldwide delivering the lowest cost data solution and best coverage of any GPS security tracking device on the market.

The **QT 1000** can be used on aircraft, cars, trucks and ships.

Device Specifications

Voltage:	9V – 36V DC
Standby Current:	<145mA @ 13.8V
Work Current:	<350mA @ 13.8V
Max Work Current:	<450mA @ 13.8V (Transient peak current 2W)
Iridium Frequency:	1616 ∼ 1626.5MHz
Output power:	1.36W
GSM Frequency:	850/1900MHZ dual-band
GPRS multi-channel level:	GPRS CLASS 10
Antenna gain:	2dBi
Hot/auxiliary/cold Start:	< 32s, < 1s, < 32s
Dimensions (mm):	86(L) x 43(W) x 113(H)
Work Temperature:	-30°C − 70°C
Work Humidity:	5% – 95% No frosting
Weight:	290 gram
IP Level:	IP 30

QT 209 EnduroTrack



Product Features

- · Live location updates OR Location on demand,
- Internal Back up Battery,
- 24/7 Online Customer Support,
- 24/7 Stolen asset recovery assistance,
- Historical Playback (bread crumb trail),
- Activity Reports (moving and stationary),
- Route optimisation (improving accuracy and reducing update times).

QT 209 EnduroTrack, EnduroTrack+, EnduroTrack++

Voltage: 6 – 36V Work Current: < 30mA @ 12V Standby Current: < 5mA @ 12V GPS Accuracy: 5m LBS Accuracy: 10m GPS Sensitivity: -159dBm GSM Frequency: 850 / 900 / 1800 / 1900MHz Quad band WCDMA Frequency: W900 / W2100MHz Hot/warm/cold Start: < 3s, < 15s, < 45s Battery Capacity: 5000mAh, 7500mAh, 9000mAh
Standby Current: < 5mA @ 12V GPS Accuracy: 5m LBS Accuracy: 10m GPS Sensitivity: -159dBm GSM Frequency: 850 / 900 / 1800 / 1900MHz Quad band WCDMA Frequency: W900 / W2100MHz Hot/warm/cold Start: < 3s, < 15s, < 45s
GPS Accuracy: 5m LBS Accuracy: 10m GPS Sensitivity: -159dBm GSM Frequency: 850 / 900 / 1800 / 1900MHz Quad band WCDMA Frequency: W900 / W2100MHz Hot/warm/cold Start: < 3s, < 15s, < 45s
LBS Accuracy: 10m GPS Sensitivity: -159dBm GSM Frequency: 850 / 900 / 1800 / 1900MHz Quad band WCDMA Frequency: W900 / W2100MHz Hot/warm/cold Start: < 3s, < 15s, < 45s
GPS Sensitivity: -159dBm GSM Frequency: 850 / 900 / 1800 / 1900MHz Quad band WCDMA Frequency: W900 / W2100MHz Hot/warm/cold Start: < 3s, < 15s, < 45s
GSM Frequency: 850 / 900 / 1800 / 1900MHz Quad band WCDMA Frequency: W900 / W2100MHz Hot/warm/cold Start: < 3s, < 15s, < 45s
WCDMA Frequency: W900 / W2100MHz Hot/warm/cold Start: < 3s, < 15s, < 45s
Hot/warm/cold Start: < 3s, < 15s, < 45s
Battery Capacity: 5000mAh, 7500mAh, 9000mAh
Dimensions (mm): 68(L) x 40(W) x 20(H)
Work Temperature: -20°C – 70°C
Work Humidity: 20% – 80% RH
Weight: 90 gram
IP Level: IP 67

QT 1100 QuikLock

QT 1100 QuikLock Technology offers a wide product range of intelligent locks in meeting the operation needs of transportation, logistic, oil, security industry, private organizations and government departments. We successfully combine realizablemechanical lock, GPS and advance wireless communication technology to make the heavy duty and high security intelligent locks. Each intelligent lock can communicate through GSM, RFID, NFC and a feature-rich.



Product Features

- Build-in rechargeable battery, no external power source required,
- Equips with GPS capabilities, reports you where it is;
- Cellular technology that communicates the lock's status to your phone;
- "Keyless" design reduces risk of loss the key and increase operation efficiency;
- Feature-rich online platform provides real time map, reports, alerts, lock status, users, supervisor records information;
- Text message or email alert on the predefined events: open, closed, tempered, locations;

Device Specifications

Voltage:	DC5V/2A
Material:	Aluminum alloy
Alarms:	Low power, Anti break, Anti theft, Drop alarm
GPS Accuracy:	UBLOX GPS, the precise scope of 10 meters
LBS Accuracy:	About 200m (Depending on density of base stations)
GPS Frequency:	L1-band (1575.42MHz)
GSM Frequency:	850 / 900 / 1800 / 1900MHz Quad band
WCDMA Frequency:	W900 / W1900 / W2100MHz
Storage:	2M Flash , >5000 blind spot data stored
Battery Capacity:	Li battery 6000MA/3.6-4.2V
Dimensions (mm):	140(L) x 102(W) x 35(H)
Work Temperature:	-30°C − 80°C
Storage Temperature:	-45°C – 85°C
Work Humidity:	95% Non condensing
IP Level:	IP 67

QT 1200 WatchTrack

OHS Technology



Main Functions



SOS alert



Auto answer



Monitor mode



Man down alarms



OHS



Heart rate



Blood pressure



GPS tracker



Remove alert



Wi-fi



Waterproof lever to IP67



SMS

Solutions

- Carers;

 - Security;
- Falls management;

Dementia:

- Retirement villages;
- Healthcare professionals.

Product Benefits

We provide market leading service, software and hardware to ensure our current and future clients are provided the best solution that is available. With our continued development and utilisation of new and improved technologies we are confident our solutions will be right for you.

Track Plan

- Lifetime Asset Recovery Assistance,
- 24/7 Response Centre Theft and Alarm support,
- 24/7 Online Technical Support,
- IMNS Sim Technology and all data (no hidden costs),
- 2 year warranty on hardware,
- In-app push and email notifications,
- App and Web portal access,
- Historical Reporting,
- Statistical Reporting,
- Unlimited live tracking (route optimisation).

Protect Plan

- Lifetime Asset Recovery Assistance,
- 24/7 Response Centre Theft and Alarm support,
- 24/7 Online Technical Support,
- IMNS Sim Technology,
- 10 Free credits upon activation,
- 2 year warranty on hardware,
- In-app push notifications (alarms)
- App access, keeping you connected!


Watch Plan

- Lifetime Asset Recovery Assistance,
- 24/7 Response Centre Theft and Alarm support,
- 24/7 Online Technical Support,
- IMNS Sim Technology and all data (no hidden costs),
- 2 year warranty on hardware,
- In-app push, email and phone call notifications (alarms),
- App and Web portal access,
- Historical Reporting,
- Statistical Reporting,
- Unlimited live tracking.

IMNS SIM Technology

Intelligent Multiple Network Switching SIM Technology is proprietory technology developed by M2M Data Services to remove the costs and difficulties associated with global roaming. IMNS removes boundaries associated with cross border applications, allowing our sims to switch seamlessly across GSM/WCDMA networks within a country, and internationally.

IMNS technology is patent protected, and exclusive to M2M Data Services, delivering you the most comprehensive and global connectivity for you and your clients.



Mobile Apps and Software



Full own branding and customization!

Our Contacts

Aust Phone: 1300 885 461

Global Phone: +1800 678 4173

E-mail: sales@m2mglobaltech.com

Web site: www.m2mglobaltech.com

